JOURNAL OF THE INDIAN INSTITUTE OF SCIENCE

EDITORIAL POLICY

The Journal of the Indian Institute of Science tries to foster the objectives of the Institute, namely, to carry out research in Science and Engineering so as to contribute to the scientific and technological progress in general and India in particular.

The following types of articles are considered for publication :

- (a) Original papers of basic and applied research.
- (b) Significant contributions on instrumentation, standardization and applications in technology.
- (c) Short communications, which require rapid publication including those concerning improvement of technique and design of scientific instruments.
- (d) Detailed papers, of which a summary or a short communication has already appeared or those summarizing the work done on a project over a period of years.
- (e) Critical reviews and surveys.
- (f) Invited articles.

EDITORIAL COMMITTEE

Editor :	Periodicity:			
N. Mukunda	Monthly			
Associate Editor : C. S. Vaidyanathan	Published in three Sections.			
	Section A (Engg. & Tech.) : Jan., Mar., May, July, Sept. & Nov.			

Executive Editor : T. K. S. Iyengar.

Scientific Assistant (Editoria!): K. Sreenivasa Rao

Members :

S. M. Deshpande

R. Narasimha

R. Rajaraman

A. K. Rao

V. V. S. Sarma

D. P. Sen Gupta

H. Sharat Chandra

K. P. Sinha

G. S. R. Subba Rao

I.S.S.N. No. 0019-4964

Section B (Phy. & Chem. Sci.): Feb., June and Oct.
Section C (Biological Sci.): Apr., Aug. and Dec.

Subscription Rates :

Country	Annual	Single Copy
India	Rs. 120	Rs. 12
UK	£ 20	£ 2
USA and rest of the world	\$ 40	\$ 4

(Overseas rates for Sea-mail service, Air-mail rates on app'ication.)

Enquiries may be addressed to :

T. K. S. Iyengar, Executive Editor, Journal of the Indian Institute of Science, C/o Library, Indian Institute of Science, Bangalore 560 012 (India). J. Indian Inst. Sci. 62 (B), Feb. 1980, Pp. 1-7 (C) Indian Institute of Science, Printed in India.

Investigation of the utility of some synthetic magnesium silicates in radioactive waste treatment

SATYA BRAT AND N. S. SUNDER RAJAN

Hi-level Waste Management Section, Bhabha Atomic Research Centre, Bombay 400 085, India.

Received on December 24, 1979.

Abstract

Three products of 'stevensite' type of clay minerals have been synthesised using different SiO₂/MgO molecular ratios at atmospheric pressure and boiling water temperature. Ion exchange studies have been carried out on these synthetic products with a view to utilise them in the treatment of low and intermediate levels of radioactive liquid wastes.

Key words : Stevensite, ion exchange, radio active wastes, sorption, phyllitic minerals, decontamination.

1. Introduction

As a followup of our earlier work on the use of various naturally occurring clay minerals^{1,2} and transformation of vermiculites of Indian origin^{3,4}, preliminary investigations carried out by Caillère and Brat⁵ have indicated promising exchange capacities of the phyllitic minerals in the sorption of cesium. Though a lot of work has been reported on the synthesis of clay minerals using silica and alumina gels⁶⁻⁹, most of the workers have synthesised the clay minerals in very small quantities, due to which even evaluation of the physico-chemical properties became difficult.

An attempt has been made to synthesise larger quantities of phyllitic minerals so that their use in the radioactive liquid waste management could be made.

2. Materials and methods

2.1. Materials

Reagents and chemicals used were of A.R. grade. Silica gel was prepared by the action of dilute hydrochloric acid on sodium silicate.

1

I.I.Sc.-1

2.2. Methods

Using silica gel containing 65 per cent SiO₂, three different experiments with SiO₂/MgO molecular ratios as 0.66, 0.88 and 1.33 were carried out. The products obtained were termed as 1, 2 and 3 respectively. Silica gels were continuously boiled with magnesium acetate solution at atmospheric pressure in 2-litre round tottomed pyrex glass flasks. Regular samples were withdrawn from the flasks and were subjected to X-ray analysis to evaluate the formation of crystalline products. As the products obtained at the end of 45 days of boiling showed good crystallinity the experiments were stopped at this stage. Products were separated free from magnesium acetate solution by repeated washings with distilled water and dried in an oven at 315° K and weighed. The products were evaluated for their physico-chemical and sorptive behaviour. Chemical analyses were carried out, following the standard methods adopted earlier by Riley¹⁰. X-ray analyses were carried out using Philips X-ray machine PW 1010, using CuK_a radiations (34 K.V., 18 m.a.) and Ni filter. Theoretical structural formulae for half-unit cell structure were calculated using the method adopted earlier by Caillère and Hénin¹¹.

Ion exchange studies were made by batch method using Boyd, Schubert and Adamson¹² model of ion exchange equilibria, with radioactive tracer Cs-134.

3. Results and discussion

3.1. X-ray analysis

Products 1, 2 and 3 show most of the prominent lines (Table I) corresponding to

Stevensite¹³ group of clay minerals. Presence of 0.152 nm value indicates the formation of trioctahedric mineral.

3.2. Equilibrium uptake capacities, weights obtained, % yield and densities

1M NaCl solution was equilibrated at $pH \simeq 6.8$. The amount of Mg⁺⁺ exchanged is given as meq/100 g. It is seen from Table II that equilibrium uptake capacities, % yield and the densities of the products synthesised go on increasing as SiO₂/MgO molecular ratio in the initial reactants is increased from 0.66 to 1.33. Equilibrium uptake capacity of Stevensite group of minerals is generally around 38 meq/100 g¹⁴. Stevensite group of minerals have density values between 2.15 and 2.20¹⁵. These values further confirm our earlier conclusion that these three products correspond to stevensite.

3.3. Chemical analysis

SiO₂/MgO molecular ratio in the case of Stevensite¹⁶ is approximately equal to 1.39. Synthetic products (Table III) fall in close proximity to this value.

RADIOACTIVE WASTE TREATMENT BY SYNTHETIC MAGNESIUM-SILICATES

Table I

Product 1		Product 2	Product 2		3	Stevensite	Stevensite (13)	
dnm	I/Io	dnm	I/lo	dnm	I/Io	dnm	I/Io	
1.22	10	1.18	10	1 • 219	10	$1 \cdot 24 \\ 1 \cdot 12 \\ 0 \cdot 50 $	10	
		0.455	0	0.450		0.49	2	
0-45 0-418	5	0.433	8	0.420	5 4	0.404	10	
				0.360	3	$\left. \begin{array}{c} 0.350\\ 0.300 \end{array} \right\}$	5	
0-258	6	0.260	8	0.260	3	0-262	9	
0.223	2					0.228	2	
0.189	8							
0.175	7	0.171	1			0.173	4	
0.164	6			0.168	1			
0.152	6	0-152	10	0-152	8	0.152	9	
		0.137	7			0-131	7	

X-ray analysis data : SiO₂-MgO reaction products

Table II

Equilibrium uptake capacities, weights obtained, % yield and densities

Product No.	Uptake capacities	Weights	Yield (%)	Densities (g/cc)		
	(meq/100 g)	(g)		Crystallo- graphic	Pycnometric	
1.	42.0	7.66	79.9	1.89	1.95	
2.	46.0	8.03	81.5	2.11	2.15	
3.	50-0	9.01	95.1	2.15	2.20	

3.4. Theoretical structural formulae

Structural formulae of Stevensite¹⁷ is represented as:

Si [Mg(3-0) R +] O10 (OH)2 CE.

Where R is a monovalent cation or vacant cation lattice site, in the latter case CE is generally equal to 2x and $x \simeq 0.1$. Structural formulae of the synthetic products 1, 2 and 3 (Table IV) agree well with the above mentioned formula of Stevensite.

Table III

Product No.	SiO ₂	MgO	Total H₂O (at 1,370° K)	Total	SiO ₂ /MgO (Molecular ratio)	 .,
	48.41	24.20	28.06	100.67	1.33	- :
2.	46-93	22.90	30.48	100.31	1 • 37	
3.	49.60	23.14	27.12	99.86	1.43	

Chemical analysis : SiO₂-MgO reaction products

3.5. Estimation of sorption capacities and selectivity coefficients

These were estimated by batch method using Cs-134 + Cs⁺ Conc. 10^{-2} M. Results of sorption capacities (F_{cs} , given in terms of meq/100 g) and selectivity coefficients (K_{Mf}^{cs}) towards Cs⁺ are given in Table V and Fig. 1. It is seen that the sorption capacity of the synthetic products 1, 2 and 3 towards Cs⁺ ion goes on increasing and the selectivity coefficient goes on decreasing with the increase in SiO₂/MgO molecular ratio from 0.66 to 1.33 in the initial reactants. Thus, product 3, with SiO₂/MgO molecular ratio = 1.33 in the initial reactants, with higher sorption capacity and decreased selectivity coefficient is better suited for the decontamination of radioactive effluents containing Cs⁺ ions.

- 4. Potential application in radioactive waste treatment

Tailor-made synthetic products with high sorption capacity and better yield can be effectively used in the treatment/disposal of radioactive liquid wastes containing radiocesium. Further, these tailor-made minerals will find an important role after a decade or so, when the natural vermiculite resources get depleted by their continuous use in radioactive liquid waste management.

5. Conclusion

The investigations on the yield of the products 1, 2 and 3 suggest that the product 3 obtained from SiO_2/MgO molecular ratio = 1.33 (in the initial reactants) gives the best yield (95 per cent). The equilibrium uptake values and the sorption capacity towards

Table IV

Chemical analysis	No. of molecules	No. of Oxygens	No. of cations	No. of ions in half lattice structure
$SiO_2 = 48 \cdot 41$	0.8068	1.6136	0.8068	4.00
$MgO = 24 \cdot 20$	0.6050	0.6020	0.6020	3.00

Theoretical structural formula : Product 1

 $N = 2 \cdot 2186.$

Taking n = 11 (i.e., No. of oxygens in half lattice structure of the dehydrated mineral). We have $n/N = 11/2 \cdot 2186 = 4 \cdot 9581$.

.: Theoretical structural formula: Si4.0 Mg.3.0 O10 (OH)2.

Using these calculations, structural formulae of products 2 and 3 have been found to be:

Product 2 : Si4-02 Mg2-95 O10 (OH)2

Product 3: Si4.07 Mg2.85 O10 (OH)2.

Table V

Sorption capacities and selectivity coefficients

(Using Cs-134 + Cs⁺ Conc. = 10^{-2} M)

Product No.	F _{cs} (meq/100 g)	K ^{Cs} _{Md}		Č≠		÷ .	
			8		٠		1
1. -	23.3	7.5					
2.	28.6	6.2					
3.	34.4	2.0					-

Cs+ ions indicate that these values increase with the increase in SiO₂/MgO molecular ratio in the initial reactants.

SATYA BRAT AND N. S. SUNDER RAJAN



FIG. 1. Relation between $(X/m)_A$ and $(X/m)_A C_B/C_A$ with Cs^+ conc. 10^{-2} M.

6. Acknowledgements

Thanks are due to Dr. A. K. Ganguly, National Fellow, D.S.T., B.A.R.C., for his guidance. Thanks are also due to Mr. K. T. Thomas, Director, Engg. Services Group, and Mr. K. Balu, Head, W.M.O. Section, B.A.R.C., for their continuous interest during the progress of this work. Authors are thankful to Mr. R. C Rastogi of H.W.M. Section for his useful suggestions.

References

- 1. SATYA BRAT et al
- 2. SATYA BRAT AND WEY, R.
- 3. SATYA BRAT
- 4. SATYA BRAT
- 5. CAILLÈRE, S. AND SATYA BRAT
- 6. CAILLÈRE, S., HÉNIN, S. AND ESTÈOULE, J.
- 7. CAILLERE, S., HENIN, S. AND BESSON, H.
- 8. WEY, R. AND SIFFERT, B.

- B.A.R.C., 1968, Report No. 349.
- Bull. Gp. Franç, Argiles, 1968, 20 (2), 69-77.
- J. Indian Inst. Sci., 1978, 60 (B) (2), 29-35. J. Indian Inst. Sci., 1978, 60 (B) (10), 185-194. Bull. Gp. Franç. Argiles, 1968, 19 (2), 39-42.
- Clay Mineral Bull., 1963, 5 (30), 272-278.
- Bull. Gp. Franç. Argiles, 1964, 14, 125-129.
- C.N.R.S., 1961, Colloquium No. 105, Paris, France.

RADIOACTIVE WASTE TREATMENT BY SYNTHETIC MAGNESIUM-SILICATES

9.	SIFFERT, B.	Carte geologique d'Alsace et de Lorraine, Université de Strasbourg, France, 1962, No. 21.
10.	RILEY, J. P.	Analytica Chimica Acta, 1958, 19, 417.
11.	Caillère, S. and Hénin, S.	Minèralogie des argiles, Masson et cie, Paris, France, 1963, p. 151.
12.	BOYD, G. E., SCHUBERT, J. AND ADAMSON, A. W.	J. Am. Chem. Soc., 1947, 69, 2818.
13.	BRINDLEY, G. W.	Am. Min., 1955, 40, 239.
14.	MACEWAN, D. M. C.	X-ray identification and crystal structures of clay minerals, by G. Brown, 1961, p. 161.
15.	Caillère, S. and Hénin, S.	Minéralogie des argiles, Masson et cie, Paris, France, 1963, p. 222.
16.	FAUST, G. T. AND MURATA, K. J.	Am. Min., 1953, 38, 975–987.
17.	CAILLÈRE, S. AND Hénin, S.	Minéralogie des argiles, Masson .t cie, Paris, France, 1963, p. 219.